

60121-013

IN THE CLAIMS

1-29. (CANCELLED)

30. (CURRENTLY AMENDED) An extendable rearview mirror assembly for a vehicle comprising:

a mount to be attached to a vehicle;

a mirror housing;

a generally rectangular mirror disposed in said mirror housing, said mirror defining a plane, and said mirror having a central axis and a longitudinal pivot axis which extends through said plane of said mirror and non-parallel to said plane of said mirror, and said longitudinal pivot axis is offset from said central axis; and

a structure for allowing rotation of said mirror about a said longitudinal pivot axis which extends through the plane of said mirror and non-parallel to the plane of the mirror, said axis being offset from a central axis of said mirror such that, and rotation of said mirror about said longitudinal pivot axis moves said mirror between an inboard position and an outboard position, said inboard position and said outboard position being disposed 90° apart from each other around said longitudinal pivot axis, said mirror having a longer dimension and a smaller dimension to define said generally rectangular shape, and said longer dimension extending generally parallel to a horizontal plane when said mirror is in said inboard position, and said longer dimension of said mirror extends generally vertical when said mirror is in said outboard position, with said outboard position being pivoted in a direction away from the vehicle from said inboard position.

31. (CURRENTLY AMENDED) The extendable rearview mirror assembly as recited in claim 30, further including a mirror shell and a biasing member for biasing said mirror housing against said mirror shell to lock said mirror at said inboard position and said outboard position.

32. (CANCELLED)

60121-013

33. (CURRENTLY AMENDED) The extendable rearview mirror assembly as recited in claim 30, wherein said longitudinal pivot axis is generally perpendicular to said plane of said mirror.

34. (CURRENTLY AMENDED) The extendable rearview mirror assembly as recited in claim 30 further including a second outboard position, and wherein said inboard position and said second outboard position are disposed 180° apart from each other around the said longitudinal pivot axis.

35. (PREVIOUSLY PRESENTED) The extendable rearview mirror assembly as recited in claim 34 wherein said outboard position is between said inboard position and said second outboard position.

36. (CURRENTLY AMENDED) The extendable rearview mirror assembly as recited in claim 30 further including a mirror shell, and said mirror housing is rotatable relative to said mirror shell ~~on~~ around said longitudinal pivot axis.

37. (CURRENTLY AMENDED) The extendable rearview mirror assembly as recited in claim ~~36~~ 30 further including a post disposed along said longitudinal pivot axis, and said mirror housing is disposed on said post.

38. (PREVIOUSLY PRESENTED) The extendable rearview mirror assembly as recited in claim 31 wherein said biasing member is a spring.

39. (NEW) The extendable rearview mirror assembly as recited in claim 30 wherein said mirror pivots away from the mount in an upwardly direction when moving from said inboard position to said outboard position, and said mirror pivots towards the mount in a downwardly direction when moving from said outboard position to said inboard position.

60121-013

40. (NEW) The extendable rearview mirror assembly as recited in claim 30 wherein said mirror has a first edge proximate to the mount and a second edge distal from the mount, and said longitudinal pivot axis is located between said central axis of said mirror and said second edge of said mirror.
41. (NEW) The extendable rearview mirror assembly as recited in claim 37 further including a retainer ring axially received on said post.
42. (NEW) The extendable rearview mirror assembly as recited in claim 30 wherein further including a first detent and a second detent, and said first detent defines said inboard position and said second detent defines said outboard position.
43. (NEW) The extendable rearview mirror assembly as recited in claim 36 further including a plurality of detents and a plurality of notches, and wherein said mirror housing includes one of said plurality of detents and said plurality of notches, and said mirror shell includes the other of said plurality of detents and said plurality of notches, and said plurality of notches selectively receive said plurality of detents.
44. (NEW) The extendable rearview mirror assembly as recited in claim 43 wherein said plurality of detents are remote from said mirror.